



M-STRIKE[®]

by **MDT**

**INDUSTRIAL TOOLS
SUPPLIER & MANUFACTURER**

www.mstriketools.com

BLACK OXIDE HEAVY DUTY OFFSET STRIKING WRENCHES - 12 POINT

OFFSET STRIKING WRENCHES

Non-reflective black oxide finish for use where non-plated products are required.

Large striking surface for surer blow contact and more efficient transmittal of force to fastener.

Short handle permits use in close quarters.

For use where extreme force is necessary to loosen or set large fasteners.

Heavy box walls provide greater torque transmission.

Offset handle clears obstructions.



INCH	MM	12	Outside Head Width 1 (in)	Head Thickness 1 (in)	Offset Height (in)	Overall Length (in)	Weight (lbs)
1		M2616SW	1-25/32	5/8	15/16	8-1/2	1.84
1-1/16	27	M2617SW	1-11/16	5/8	15/16	8-1/2	1.84
1-1/8		M2618SW	1-11/16	5/8	15/16	11	1.79
1-3/16	30	M2619SW	2-1/16	13/16	13/16	10-3/4	2.55
1-1/4		M2620SW	1-7/8	13/16	13/16	10-3/4	2.58
1-5/16		M2621SW	1-7/8	13/16	13/16	11-1/2	2.59
1-3/8	35	M2622SW	2-25/64	1	1-1/2	12	3.40
1-7/16		M2623SW	2-3/16	1	1-1/2	12	3.29
1-1/2	38	M2624SW	2-3/16	1	1-1/2	12	3.35
1-9/16		M2625SW	2-21/32	1-1/8	1-7/16	12-1/4	3.89
1-5/8		M2626SW	2-13/32	1-1/8	1-1/2	12-1/4	4.00
1-11/16	43	M2627SW	2-13/32	1-1/8	1-1/2	13-7/16	3.88
1-3/4		M2628SW	2-19/32	1-3/16	1-9/16	13-7/16	3.90
1-13/16		M2629SW	2-21/32	1-3/16	1-9/16	13-7/16	5.30
1-7/8		M2630SW	2-27/32	1-1/4	1-21/32	13-7/16	5.24
1-15/16		M2631SW	2-27/32	1-1/4	1-7/8	13-7/16	5.20
2	51	M2632SW	2-27/32	1-1/4	1-21/32	13-7/16	5.16
2-1/16		M2633SW	3-1/8	1-1/4	2	13-1/2	6.82
2-1/8	54	M2634SW	3-1/8	1-1/2	2	13-7/8	6.71
2-3/16		M2635SW	3-3/8	1-1/2	2	13-1/2	6.78
2-1/4	57	M2636SW	3-3/8	1-1/2	2	13-1/2	6.30
2-5/16		M2637SW	3-3/8	1-1/2	2	13-1/2	7.94
2-3/8		M2638SW	3-3/8	1-1/2	2	13-1/2	7.86
2-7/16		M2639SW	3-13/16	1-1/2	2-1/4	13-1/2	7.67
2-1/2	64	M2640SW	4	1-1/2	2-1/4	13-1/2	7.62
2-9/16		M2641SW	4	1-1/2	2-1/4	13-1/2	13.43
2-5/8		M2642SW	4	1-1/2	2-1/4	13-1/2	10.42
2-11/16		M2643SW	4-7/32	1-1/2	2-1/4	13-1/2	10.25
2-3/4		M2644SW	4-7/32	1-1/2	2-1/4	13-1/2	10.18
2-7/8	73	M2646SW	4-25/32	1-7/8	2-5/8	16	13.84
2-15/16		M2647SW	4-7/16	1-7/8	2-5/8	16	13.6
3		M2648SW	4-7/16	1-7/8	2-5/8	16	13.44
3-1/16		M2649SW	4-25/32	1-7/8	2-5/8	16	13.37
3-1/8		M2650SW	4-7/16	1-7/8	2-5/8	16	13.18
3-3/8		M2654SW	6-1/4	2-3/8	3-5/8	18	26.88
3-1/2		M2656SW	6-1/4	2-3/8	3-5/8	18	26.37
3-3/4		M2660SW	6-1/4	2-3/8	3-5/8	18	25.03
3-7/8		M2662SW	6-1/4	2-3/8	3-5/8	18	24.58
4-1/8		M2666SW	6-1/4	2-3/8	3-5/8	18	23.47
4-1/4		M2668SW	6-1/4	2-3/8	3-5/8	18	22.75



BLACK OXIDE HEAVY DUTY METRIC OFFSET STRIKING WRENCHES - 12 POINT

Non-reflective black oxide finish for use where non-plated products are required.

12 point box end allows for fine indexing, helping improve speed and access.
Fits most 4, 6 and 12 point fasteners.

Large striking surface for surer blow contact and more efficient transmittal of force to fastener.

Short handle permits use in close quarters.

For use where extreme force is necessary to loosen or set large fasteners.

Heavy box walls provide greater torque transmission.

Offset handle clears obstructions.



MM	12	Outside Head Width 1 (in)	Head Thickness 1 (in)	Offset Height (in)	Overall Length (in)	Weight (lbs)
27	M2617SW	1-11/16	5/8	15/16	8-1/2	1.84
32	M2632SWM	1-57/64	53/64	1-3/16	10-3/4	0.88
36	M2636SWM	2-13/64	63/64	1-1/2	12-1/64	2.13
41	M2641SWM	2-13/32	1-7/64	1-1/2	12-1/4	2.37
46	M2646SWM	2-43/64	1-3/16	1-37/64	13-27/64	2.81
50	M2650SWM	2-53/64	1-17/64	1-21/32	13-27/64	6.36
55	M2655SWM	3-25/64	1-1/2	2-1/64	13-1/2	6.58
60	M2660SWM	3-25/64	1-1/2	2-1/64	13-1/2	9.19
65	M2665SWM	4-1/64	1-1/2	2-1/4	13-1/2	12.61
70	M2670SWM	4-1/64	1-1/2	2-1/4	13-1/2	12.11
75	M2675SWM	4-29/64	1-57/64	2-41/64	16-1/4	13.53
80	M2680SWM	4-29/64	1-57/64	2-41/64	15-63/64	13.16



BLACK OXIDE HEAVY DUTY STRIKING WRENCHES - 6 POINT

Non-reflective black oxide finish for use where non-plated products are required.

Large striking surface for surer blow contact and more efficient transmittal of force to fastener.

Short handle permits use in close quarters.

For use where extreme force is necessary to loosen or set large fasteners.

Heavy box walls provide greater torque transmission.

Straight handle design helps prevent the wrench from cocking when struck.



INCH	6	Outside Head Width 1 (in)	Head Thickness 1 (in)	Overall Length (in)	Weight (lbs)
1-1/16	M2717SW	1-25/32	5/8	9-7/8	1.62
1-1/4	M2720SW	2	23/32	10-1/4	1.72
1-7/16	M2723SW	2-17/64	7/8	10-19/32	2.49
1-5/8	M2726SW	2-31/64	61/64	10-15/16	3.17
1-13/16	M2729SW	2-21/32	63/64	11-5/16	3.49
2	M2732SW	3-1/32	1-7/32	11-21/32	4.73
2-3/16	M2735SW	3-9/32	1-15/64	11-5/16	5.33
2-3/8	M2738SW	3-13/32	1-7/16	12-3/8	5.63
2-9/16	M2741SW	3-3/4	1-17/32	12-11/16	6.47
2-3/4	M2744SW	4-11/64	1-17/32	12-13/16	7.56
2-15/16	M2747SW	4-23/64	1-17/32	13-5/16	7.81
3-1/8	M2750SW	4-31/64	1-41/64	13-11/16	9.50
3-1/2	M2756SW	4-31/32	1-23/32	13-29/32	10.54
3-7/8	M2762SW	5-35/64	1-23/32	14-13/32	12.76

